



Owner's Manual – Dri-Eaz TurboDryers

230-volt Models

Sahara, Sahara Pro, Sahara Compact, Vortex, Santana SX, Ace

DRI-EAZ PRODUCTS, INC.

15180 Josh Wilson Road, Burlington, WA USA 98233

Fax US: (360) 757-7950 Phone US: (360) 757-7776 Phone UK: (01908) 611211 www.dri-eaz.eu.com

TurboDryers are high-performance airmovers for speed-drying of building structures and contents. They are designed for a balance of static pressure and airflow, as well as durability and ease of use.

Read And Save These Instructions



Safety Information

Keep Children Away: Do not allow children to play with or around the unit, which could result in injury. Be sure the unit is inaccessible to children when not attended.

Keep Unit Grounded: Always operate the unit with a grounding plug and a grounded electrical outlet. A grounding plug is an essential safety feature that helps reduce the risk of shock or fire.

Protect Power Cord from Damage: Never operate a unit with a damaged power cord, as this may lead to electrical or fire hazards. If the power supply cord is damaged, it must be replaced by a cord of the same type and amperage rating.

Extension Cords: Extension cords must be grounded and able to deliver the appropriate voltage to the unit.

Do Not Use Speed Control Device: To reduce the risk of fire or electric shock, do not use TurboDryers with a solid-state speed control device.

Handle With Care: Do not drop or throw the unit. Rough treatment can damage the components or wiring and create a hazardous condition.

Run on Stable Surface: Always operate the unit on a stable, level surface, like the floor or a strong counter, so it cannot fall and cause injury.

Secure During Transport: When transporting in a vehicle, secure the unit to prevent sliding and possible injury to vehicle occupants.

Keep Out of Water: Never operate the unit in pooled or standing water, as this may create a risk of injury from electrical shock. Do not store or operate outdoors. If electrical wiring or components become wet, thoroughly dry them before using the unit.

Keep Air Intakes Clear: Do not clog or block air intakes, as may occur if operated too close to draperies or similar materials. This may cause the unit to overheat and result in a fire or electrical hazard.

Keep Out Dust and Dirt: Do not allow dust, dirt, or other particles to be drawn into the air intakes. Dirt in the motor

can cause it to overheat, resulting in a fire or electrical hazard. If the motor gets dirty, clean it using an air hose.

Allow Repair Only by Qualified Person: Do not attempt to disassemble or repair the unit if you are not qualified to do so. You may handle some maintenance and troubleshooting, but make sure that more complex problems are handled by an authorized service technician. For information about authorized repair, call the Dri-Eaz UK office at (01908) 611211.

HOW TO USE TURBODRYERS

TurboDryer airmovers are designed to blow air across wet surfaces for speed drying. They are especially good for drying floors because they create a flat ribbon of air. High-volume airflow will increase the rate of evaporation, help prevent mould growth, and reduce the risk of additional moisture damage. Moving air will improve evaporation by removing a boundary layer of saturated air that hangs near wet surfaces. TurboDryers whisk away this moist air and replace it with dryer air.

Positioning TurboDryers

When drying in a building, place at least one TurboDryer per room, or one for every 200 square feet. Place as many as needed for maximum airflow across all wet areas of the floor.

Ensure that all wet surfaces receive good airflow. Open interior doors to maintain good air circulation. Doors may need to be braced to prevent them from blowing shut.

Control the Humidity

Using TurboDryers to speed the rate of evaporation in a building usually causes the humidity to rise immediately. When this occurs, the air movement becomes less effective and the rate of drying slows. It is vital that TurboDryers be used with adequate dehumidification. To help control mould growth, keep indoor humidity below 60% Rh. If possible, maintain indoor humidity below 45% Rh. This may require the use of DrizAir Refrigerant Dehumidifiers. Even lower humidity (25-40% Rh) will speed the drying of dense materials such as lumber, and is possible with Dri-Eaz Desiccant Dehumidifiers.

To improve drying, close off the area being dried from the rest of structure. Regulate the heating or air conditioning system at 68-80°F (20-27°C). When dehumidifiers are not available, run exhaust fans in the attic, kitchen and bathroom to remove some humidity. If outdoor air is very dry, open some windows or doors at least slightly. Use a thermo-hygrometer to determine the relative humidity.

Check if Materials are Dry

Monitor the moisture condition of wet materials with moisture meters like the HydroSensor, Moisture Counter, and Moisture Pro. To check how completely materials have dried out, compare your readings to readings you take on similar materials you know are dry.

Cooling & Ventilation

Over-heated rooms can be cooled with high-volume airflow from a TurboDryer. Place the airmover on the floor or other flat surface and direct the air from cooler areas or the outdoors. Use the kickstand or the 45-90 degree tilt feature to elevate the snout and circulate cool air throughout the room.

OPERATING INSTRUCTIONS

1. Plug in to a standard outlet with the correct voltage and amperage for the unit. Set the switch at the desired speed. Check for proper operation before leaving the unit unattended.
2. Do not move or carry the TurboDryer when it is running.

ELECTRICAL CONNECTIONS

TurboDryers are designed to operate on a 230V/50 Hz electrical connection. Make sure that the electrical outlet is grounded and that all safety precautions are taken.

MAINTENANCE

Always turn off the power before performing maintenance procedures. All the service procedures below are to be executed with the unit unplugged. Perform before each use or as needed.

INSPECT ELECTRICAL SYSTEM: Inspect the electrical cord for damage at regular intervals. Periodically, remove the housing and inspect internal wiring for bare wires, insecure fasteners, and discoloration. Remove and repair any damaged wiring as needed. Failure to do so may lead to electrical shock or a fire hazard.

CLEAN AIR INTAKES: Clean off any accumulated lint or other materials from the air inlet side-screens. A buildup will reduce the airflow and may cause the motor to overheat and become a fire hazard.

CLEAN EXTERIOR: Clean the housing with mild detergent and water. Bring back the original shine with a vinyl cleaner and polish like those used on automobile plastics.

EXTERIOR INSPECTION: Evaluate exterior components and make sure they are properly installed. Listen to the unit for abnormal sounds. Repair or replace components as needed.

Periodic Maintenance (as needed)

Make sure unit is unplugged and the wheel has stopped. Remove four screws to remove each side screen. This will permit access to motor and wheel for cleaning.

CLEAN COMPONENTS: Use compressed air or a vacuum to remove lint and dust from blower wheel, motor and side screens.

DO NOT WET MOTOR OR WIRING: To prevent damage to electrical components, do not use a hose or pressure washer to clean a TurboDryer. If electrical components do become wet, dry them immediately.

MOTOR BEARINGS: The bearings on all Dri-Eaz TurboDryers are permanently lubricated. Do not oil.

WARRANTY

See separate warranty card for full warranty details.

TO RECEIVE WARRANTY SERVICE: You must write or call for an RMA (Return Material Authorization). You must have the serial number available. The Dri-Eaz Service Department must authorize all costs, including carriage, for any Service Centers worldwide. Please direct questions to an authorized distributor, or to Dri-Eaz UK at (01908) 611211.

SPECIFICATIONS

Model	SAHARA	SAHARA PRO	SANTANA SX	SAHARA COMPACT	ACE	VORTEX
Switch	2-Speed Rocker	3-Speed Rotary	2-Speed Rocker	2-Speed Rocker	2-Speed Rocker	1-Speed Rocker
Actual CFM (max)	1340 cfm	1360 cfm	877 cfm	402 cfm	2000 cfm	1679 cfm
	2233 cmh	2310 cmh	1490 cmh	683 cmh	3398 cmh	2798 cmh
Rated CFM (max)	3100 cfm	2,700 cfm	900 cfm	N/A	2250 cfm	N/A
	5267 cmh	4,600 cmh	1529 cmh		3823 cmh	
Static Pressure	56mm, 2.2"	56mm, 2.2"	21.6mm, .85"	15mm, .6"	25mm, 1"	58 mm, 2.3"
Power, 230 Volts	3.3 amps	3.7 amps	1.3 amps	1.0 amp	1.0 amp	2.2 amps
Carpet Clamp	Kit Available	Yes	Kit Available	N/A	N/A	N/A
Kickstand	Yes	Yes	Yes	N/A	N/A	N/A
Positions	3	4	4	1	7	1
Height,Width,Length	20", 17.5", 20"	20", 17.5", 20"	19", 16", 21"	15", 12", 12"	20", 15", 20"	19", 19",16"
	50, 44, 50 cm	50, 44, 50 cm	48, 41, 53 cm	38, 29.5, 30 cm	50, 44, 50 cm	49, 48, 40 cm.
Use Weight	17 kg, 38 lb	17 kg, 38 lb	11 kg, 25 lb	4.1 kg, 9 lb	13 kg, 28 lb	15 kg, 33 lb
Ship Weight	19.5 kg, 43 lb	20 kg, 44 lb	16 kg, 35 lb	4.5 kg, 10 lb	16 kg, 35 lb	19 kg, 41 lb
Motor Rating	.56 kw/.75 hp	.56 kw/.75 hp	.15kw/.2 hp	.08 hp	.4 hp	1.0 hp
Overheating Cutoffs	Dual Thermal	Dual Thermal	Dual Thermal	Dual Thermal	Dual Thermal	Dual Thermal
Safety Listings	CE	CE	CE	CE	CE	CE

Specifications are subject to change without notice. Some values are approximate.

TROUBLESHOOTING

In COLUMN 3, the technician in the field can handle "FS" or Field Solutions. Others solutions should be handled by a repair technician – an "AST" or Authorized Service Technician.

WARNING: Execute all the service procedures below only with power turned off, i.e. unplugged.

PROBLEM	CAUSE	See above	SOLUTION
Motor won't run	No power to machine	FS	Plug in the unit; check circuit breaker or fuse
	Switch not turned on	FS	Turn on the switch
	Blower wheel jammed	FS	Remove material jamming wheel
	Intake or exhaust blocked	FS	Turn machine off and allow to cool, then remove blockage
	Switch is broken	AST	Call distributor or Dri-Eaz for replacement switch
	Loose wiring	AST	Check wiring and tighten as needed
Motor runs but wheel turns erratically or scrapes	Severe jolt has caused motor mount to bend and wheel to rub	AST	Remove motor from housing, then replace or repair bent motor mount
	Severe jolt caused motor to slip out of mount and wheel to rub	AST	Remove motor from housing, then install motor into mount correctly
Unit vibrates excessively	Accumulation of soil on wheel	FS	Clean blower wheel
	Blower wheel has lost balance	AST	Balance or replace blower wheel
	Blower wheel has been bent	AST	Replace blower wheel
	Bent motor shaft	AST	Replace motor

FOR PARTS AND SERVICE CALL Service at Dri-Eaz Products Ltd in the UK at (01908) 611211