

Heat Gun

HG6531C

2 000 W • 200 – 550 l/min • 50 – 650 °C

Heat gun with electronic control and variable heat and airflow settings

An electronic 2 000 W heat gun for demanding use in a wide range of applications, including paint stripping. The heat gun has an adjustable heat range of between 80° and 650°C and pre-set heat and air flow settings. It is also equipped with four different nozzles.



■ Technical specifications

| | |
|---------------------------------|-------------------|
| Continuous Input Power 240V | 2000 W |
| Maximum Flow Rate | 200 - 550 L/min |
| Temperature Range | 50 - 650 °C |
| Max. Temperature | 650 °C |
| Variable Temperature | ✓ |
| Thermal Safety Switch | ✓ |
| Weight Without Cable | 0,71 kg |
| Product Dimensions (L x W x H): | 257 x 85 x 206 mm |
| IEC Protection Class | II |
| Power Supply Cord | 2,0 m |

■ User benefits

- Variable temperature control
- The rubber coating on the handle ensures a firm working grip
- Variable speed control dial enables user to match the speed to the application for greater versatility
- With overheat protection

[Link to product - www.makita.com](http://www.makita.com)



Related products

Optional AC

PR00000029

Wide Slot Nozzle, 50 mm



PR00000030

Reflection Nozzle, 40 mm



PR00000031

Reduction Nozzle, 20 mm



PR00000036

Welding Rods, ABS, 5 x 230 mm, 10



PR00000037

Welding Rod, HDPE, 10 pcs



PR00000038

Welding Rod, PP, 10 pcs



Other

[User manual](#)

[Parts drawing](#)