

GP360D

Ground Lowering, Anti-Vandal, Robust and Easy-To-Use Single Axle Mobile Welfare Accommodation Unit.

HIRElink^{UK}
(MIDLANDS LTD)
Tool Hire Centres



HSE & CDM COMPLIANT

STANDARD

MOBILE

SEATS UP TO
6 PEOPLE



INNOVATION THAT WORKS.



Seating area



Toilet wash area



Warm Room



Delivery of hot water



Well equipped canteen

Comfortable, Compact and HSE compliant.

The **GROUNDHOG** mobile GP360D is a lightweight and compact towable unit that meets HSE & CDM requirements and provides all your on-site needs in one small package.

The units are suitable for accommodating six people, which provides pleasant and safe working environments, ideal for rental companies and contractors.

Easily towed, one man operation secured and manoeuvred on site, in less than 3 minutes. Its many safety features make it a **high secure and money saving choice of welfare unit.**



Recycled non-slip flooring



Fully hot-dipped galvanised chassis



230V 1kW air blown heater



Warm water from an on-board heating system



240V LED 600mm strip light



230V single 2Amp socket



Welded boss for removable low level lifting eyes



Fuel Active system




Lowered & secured in 3 minutes

KEY FEATURES at a glance

Length	3655 mm
Length (including drawbar)	4920 mm
Height (on wheels)	2.9 m
Height (on ground)	2.5 m

Generator	6 kVA
Unladen Weight	1700 kg
Possible Gross Weight	1800 kg*
Solar Panel	N/A

Fresh Water	20 Litres
Waste Water	20 Litres
Toilet Tank Size	280 Litres
Fuel Tank Size	58 Litres



1 Canteen Area

- Table and bench seating for up to 6 people
- 240V 600mm strip light
- 230V 1kW air blown heater
- Warm water supplied by on-board heating system
- Large stainless steel sink c/w warm water tap
- 230V single 2Amp socket outlet
- Generator start panel c/w hour run meter
- Fresh & waste water containers (20 Ltr cap each)
- 12V pump for water system
- Carbon monoxide monitor and smoke alarm

2 Toilet Area

- Plastic recirculating toilet
- 12V LED lighting with PIR
- Forearm wash basin c/w warm water tap
- Warm water supplied by on-board heating system

3 Generator/ Warm Room

- Bulkhead light 240V
- 240V tubular heater
- Access to fuel tank with separate fuel level gauge (58 Ltr cap)
- Ventilation panel
- Fuel Active system
- Fuel tank runtime = approx. 25 hours

Secured in less than 3 minutes

Easily towed, one man operation secured and manoeuvred on site.

Fast deployment time means more time on the job, making it the money saving choice of welfare unit for rental companies and contractors.



Unhitch from towing vehicle and operate hydraulics using the push button controls



Lower unit to the ground and unplug controls



Close & lock canopy to protect towing facility

0 mins

3 mins

* Fully laden gross weight exceeds maximum towing capacity, unit should be transported to site prior to making site ready.